
MV-ACCL-SDR-MDR-AOC

Camera Link AOC Cable

Camera Link AOC Cable can be used for data transmission of Camera Link interface cameras, and is available in a variety of lengths.




Applicable Camera

- Hikrobot Camera Link Interface Area Scan Camera
- Hikrobot Camera Link Interface Line Scan Camera

Order Models

- 8m Camera Link SDR-MDR AOC Cable: MV-ACCL-SDR-MDR-AOC-8m-Base
- 8m Camera Link SDR-MDR AOC Cable: MV-ACCL-SDR-MDR-AOC-8m-Full
- 15m Camera Link SDR-MDR AOC Cable: MV-ACCL-SDR-MDR-AOC-15m-Base
- 15m Camera Link SDR-MDR AOC Cable: MV-ACCL-SDR-MDR-AOC-15m-Full

Dimension



Specification

Specifications \ Model	MV-ACCL-SDR-MDR-AOC
	Camera Link AOC Cable
Physical specification	
End A connector	SDR26
End B connector	MDR26(Board side with Type A USB3.0 power take-off connector)
Cable diameter	5.6 ± 0.2 mm
Length	8/15 m
Cable mechanical	Fiber*2C+(37/0.1)*1C+AL+B
Jacket	TPU
Cable color	Black
Connector durability	1000 cycles
Min. bending radius	When installed: 100 mm When used: 67.2 mm
Allowable tensile force	When installed: 300 N When used: 150 N
Allowable crushing force	Long term: 200 N/100 mm Short term: 350 N/100 mm
Applicable scenario	Drag chain
Max. U-type bending cycles	5 million times
Electrical specification	
Power supply	Base：5 V-400 mA Full：5 V-600 mA
Additional information	
Working temperature	0°C ~ 70°C
Packaging	Individual package and paper box

Read the user manual for the camera including the precautions before connecting the cable to the camera.

© Hangzhou Hikrobot Co., Ltd. All Rights Reserved.
Hangzhou Hikrobot does not tolerate any infringement. Any organization or individual may not imitate or reproduce in whole or in part of the content. The data herein is based on Hikrobot's internal evaluation. Actual data may vary depending on specific configuration and operating condition. The information herein is subject to change without notice All the content has been checked conscientiously. Nevertheless, Hikrobot shall not be liable to damages resulting from errors, inconsistencies or omissions.