MV-DP3470-01P

3D Laser Profile Sensor



Introduction

With built-in high-accuracy algorithm, image process algorithm of wide dynamic range, and data integration algorithm, MV-DP3470-01P can output high accurate 3D point cloud data in real-time by combining high frame rate chip and accurate laser control. With compact structure, high integration, and easy operation, it is widely applied into consumer electronics, electronics manufacturing, automobile, etc.

Available Model

MV-DP3470-01P V2.0


Applicable Industry

Consumer electronics, electronics manufacturing, automobile, etc.


Key Features

- Built-in high-accuracy algorithm and accuracy is up to submicron level.
- Adopts high frame rate chip with 46.7 kHz scan frame rate.
- Supports multiple exposure modes with good robustness.
- Adopts multiple-frame integration technology to provide complete profiles.
- Provides multiple filter modes with stable data.
- Supports ROI selection and auto setting for easier operation.

Dimension



Measurement Range Diagram



Specification

Model / Parameter	MV-DP3470-01P 3D Laser Profile Sensor
Performance	
Data points/profile	3200
Reference distance	565 mm
Measurement range (Z-axis)	670 mm
Measurement range (X-axis)	142 mm @ near field of view 315 mm @ reference distance 488 mm @ far field of view
Resolution (Z-axis)	10.39 μm to 169.79 μm
Repeatability (Z-axis)*	4.45 μm @ data that sensor tests gauge block on optical platform
Linearity Z-axis (±% of MR)	0.01
Profile data interval	43.9 μm to 177.4 μm
Scan frame rate	3.4 kHz to 46.7 kHz (high frame rate mode)
Data output	Profile data, depth image, brightness image
Trigger mode	Software trigger, hardware trigger (differential encoder)
Laser safety class	Class 3B
Wavelength	405 nm
Electrical feature	
Data interface	Gigabit Ethernet (1000 Mbit/s), compatible with Fast Ethernet (100 Mbit/s)
Digital I/O	12-pin M12 connector provides power and I/O, including opto-isolated input × 2 (Line 0/9), differential input × 2 (Line 3/6), differential output × 1 (Line 1)
Power supply	24 VDC
Power consumption	Typ. 17.2 W @ 24 VDC
Mechanical	
Dimension	185.5 mm × 125.5 mm × 59 mm (7.3" × 4.9" × 2.3")
Weight	Approx. 1450 g (3.2 lb.)
Ingress protection	IP67
Temperature	Working temperature: 0 °C to 45 °C (32 °F to 113 °F) Storage temperature: –30 °C to 80 °C (–22 °F to 176 °F)
Humidity	20% RH to 85% RH (no condensation)
General	
Client software	3DMVS, VM3D, or third-party software
Operating system	32/64-bit Windows 7/10, 64-bit Windows 11 (8 GB memory and above, and i5 CPU recommended)

**This data is obtained via testing gauge blocks in a laboratory, and it is an average from 4096 tests.*

Hangzhou Hikrobot Co. Ltd.
en.hikrobotics.com

© Hangzhou Hikrobot Co., Ltd. All Rights Reserved.
Hangzhou Hikrobot does not tolerate any infringement. Any organization or individual may not imitate or reproduce in whole or in part of the content. The data herein is based on Hikrobot's internal evaluation. Actual data may vary depending on specific configuration and operating condition. The information herein is subject to change without notice All the content has been checked conscientiously. Nevertheless, Hikrobot shall not be liable to damages resulting from errors, inconsistencies or omissions.